

Innovative Instruments, Inc.

8533 Queen Brooks Ct. Tampa, FL 33637. USA

Tel. 813-727-0676. Fax: 813-914-8686. www.2in.com

Available *Leak-Free* Reference Electrodes

All electrodes are Ag/AgCl/Saturated KCl

Temperature range: 0-90 C

Standard lengths. Longer or Shorter are Available Upon Request

All electrodes bodies are made of **PEEK**, Polyether ether ketone.

Part number	Diameter, mm	Barrel Length, mm	Total Length, mm	Connector*, diameter, mm
LF-05-XX	0.5	customized, XX	customized	customized
LF-1-100	1.0	100	120	1
LF-1-45	1.0	45	65	1
LF-1.6-48	1.6	48	68	1
LF-1.6-100	1.6	100	120	1
LF-2-45	2.0	45	65	1
LF-2-100	2.0	100	120	1
LF-3.2-XX	3.2	customized	customized	1
LF-5-100	5.0	100	135	1 or 2
LF-6.4-65	6.4	65	100	Wire**

*1 mm gold-plated connector, 6 mm long. Also available, 2 mm gold-plated connector, 9 mm long. BNC and other connectors can be used.

** Multi-stranded wire. 24 AWG 19/36. Insulated, 1.4 mm OD

Innovative Instruments, Inc.

Samples of *Leak-Free* Reference Electrodes



LF-2
2 mm OD
45 mm barrel



LF-1.6
1.6 mm OD
48 mm barrel



LF-1
1 mm OD
100 mm barrel



LF-5
5 mm OD
100 mm barrel

